

Technical drawing of a rectangular structure, likely a foundation or base, showing dimensions and section lines.

**Dimensions:**


- Overall width: 1700
- Inner width: 1400
- Side margins: 150 (on both sides)
- Overall height: 800
- Inner height: 620
- Bottom margin: 30
- Base width: 1200\*

**Section Lines:**

- Section line 1 (horizontal) is shown at the top and bottom.
- Section line 2 (vertical) is shown on the left side.



**Internal Features:**

- A central vertical slot or opening is located in the middle of the structure.
- Arrows indicate internal flow or forces: two horizontal arrows pointing outwards from the center, and one vertical arrow pointing upwards from the center.



Поз.	Обозначение	Наименование	Кол-во	Масса ед. кг	Примечан.
		Прямо́к Пр1	1		
С1	ГОСТ 8478-81*	С $\frac{5Bp \text{ I-100}}{5Bp \text{ I-100}}$ 750x2600	2	6,03	12,06
С2	ГОСТ 8478-81*	С $\frac{5Bp \text{ I-100}}{5Bp \text{ I-100}}$ 1500x720	1	3,34	3,34
1	ГОСТ 5781-82*	Ø12AIII L=500	6	0,444	2,664
2	ГОСТ 10704-91*	труба дн=50х3, L=500	1	3,5кг	
		Материалы:			
	ГОСТ 26633-00	Бетон кл. В12,5 м3	0,5		

1. Данный лист рассматривать совместно с листом АС-3
2. Боковые поверхности прямков, соприкасающиеся с грунтом, обмазать битумом на 2 раза по золотной грунтовке.
3. \* – Размеры уточнить по месту
4. Объемы даны на один прямок. Количество прямков – 6 шт.
5. Размеры уточняются по месту

					2019	65.17.008-2019-АС		
						Капитальный ремонт фасадов многоквартирного жилого дома, расположенного по ул. Украинская, д. 123 в г. Южно - Сахалинске		
Изм.	Кол.уч	Лист	№ док	Подп.	Дата			
						Стадия	Лист	Листов
ГИП		Елисеенко А				Р	9	
Разработал		Елисеенко А				ООО "ХОЛОДСЕРВИС" г.Южно-Сахалинск		
Прямак Пр-1								